

LANmark Industry patch cord RJ45 IP67/IP20 Cat.6

LANmark Industry patch cord RJ45 IP67/IP20 Category 6 screened PVC 5m Yellow

Nexans ref.: N10i.E34HJ

- Industrial Patch Cord RJ45 Cat 6
- One end with IP67 protection Level (Dust/liquids) - IP20 on the other end
- Suitable for the LANmark Industry IP65/67 outlet Cat 6
- Cable with good mechanical performance and resistant to chemicals
- Conform with the requirements of the ISO/IEC24702 and IEC 61076-3-106 (8way Industrial connector)
- Fully screened

Description

Application

The LANmark Industry IP67/IP20 Patch Cord is designed to be used together with the LANmark Industry IP65/67 outlet. Within industrial and harsh areas, it will provide a secure connection free of liquids and dust.

The IP20 end of the patch cord can be connected to any IT or industrial equipment featuring a standard RJ45 port.

LANmark Industry patchcords can be used to deliver a full end-to-end Class E solution in industrial areas.

Performance

- High Speed patchcords
- Reliable connections
- Full compliance to ISO/IEC24702 (Generic Cabling - industrial premises)

The LANmark Industry patch cords have been designed to reach the highest performance in Class E. They show excellent performance for attenuation (insertion loss), NEXT/FEXT, Power Sum NEXT/FEXT and Return Loss as defined in ISO/IEC 11801:2002.

This provides improved data throughput.

As such it supports all data applications defined for Cat 5, Cat 5E and Cat 6, such as:

- 10baseT
- Fast Ethernet
- Gigabit Ethernet
- 155 ATM
- 622 ATM
- 1.2 ATM
- **Industrial Ethernet.**

The IP67/IP20 end of the patchcords features a Push-Pull boot. It provides the IP67 protection level as well as a locking system for the cords. The cords can only be removed from the outlet when the user pulls on the boot. The cords can't be removed just by pulling the cable. This Push-Pull locking boot is compliant with the ISO/IEC24702 and IEC 61073-3-106 (8way industrial connector).



LANmark
Industry

Standards


International IEC 61076-3-106;ISO/
IEC 11801;ISO/IEC 24702



Lead free
Yes




Electro magnetic interference
resistance
Yes



Operating temp.
range
-10 .. 80 °C



Weather
resistance
Good



Chemical
resistance
Excellent



RoHS conform
Yes



Flame retardant
IEC 60332-1-2

LANmark Industry patch cord RJ45 IP67/IP20 Cat.6

LANmark Industry patch cord RJ45 IP67/IP20 Category 6 screened PVC 5m Yellow

Installation

- Cable with very good chemical and mechanical performances.
- Lengths available: 1,5 - 3,0 - 5,0 and 10m.
- IP67 single end cord of 10m available.
- Rugged construction.
- High connector retention force due to special boots.
- External strain relief
- IP67 Push-Pull locking system



Lead free
Yes



Electro magnetic interference
resistance
Yes



Operating temp.
range
-10 .. 80 °C



Weather
resistance
Good



Chemical
resistance
Excellent



RoHS conform
Yes



Flame retardant
IEC 60332-1-2

LANmark Industry patch cord RJ45 IP67/IP20 Cat.6

LANmark Industry patch cord RJ45 IP67/IP20 Category 6 screened PVC 5m Yellow

Nexans ref.: N10i.E34HJ

Characteristics

Construction characteristics	
Type of cable	S/FTP
Individual screen	Aluminium / Polyester tape
Overall screen	Tinned copper braid
Inner sheath	None
Outer sheath	PVC
Sheath colour	Yellow
Lead free	Yes
Connector type	RJ 45
Dimensional characteristics	
Number of pairs	4
Outer Diameter	6.5 mm
Approximate weight per piece	0.35 kg
Electrical characteristics	
Maximal operating frequency	250 MHz
Characteristic impedance	100 Ohm
Mechanical characteristics	
Abrasion resistance	High
Usage characteristics	
Component function	Cabling and Connectivity solutions
Field of application	Fixed installations
Category	Cat. 6
Length	5 m
Mechanical durability/matings	750
Electro magnetic interference resistance	Yes
Operating temperature, range	-10 .. 80 °C
Weather resistance	Good
Chemical resistance	Excellent
Packaging	Plastic bag
RoHS conform	Yes
Flame retardant	IEC 60332-1-2


Lead free
Yes

Electro magnetic interference
resistance
Yes

Operating temp.
range
-10 .. 80 °C

Weather
resistance
Good

Chemical
resistance
Excellent

RoHS conform
Yes

Flame retardant
IEC 60332-1-2